



## Approval of the Trademark Trevira CS®

Zimmer + Rohde GmbH  
 Zimmersmühlenweg 14-18  
 61440 Oberursel  
 Germany

|  |                              |
|--|------------------------------|
| <b>Application No.:</b>                  | 210424.2                     |
| <b>Date of issue:</b>                    | 27.09.2024                   |
| <b>Valid until:</b>                      | 17.06.2026                   |
| <b>Article name:</b>                     | 10663                        |
| <b>End use:</b>                          | Drapes<br>Upholstery fabrics |
| <b>Square weight (g/m<sup>2</sup>):</b>  | 454                          |
| According to customer specification      |                              |
| <b>Composition of the raw materials:</b> | Polyester 100%               |
| <b>Composition of the fabric:</b>        | Trevira CS 100%              |

The article 10663 has been tested under the Trevira trademark application no. 210424 and is granted approval for the trademark Trevira CS® for interior use.

The article was tested according to DIN 4102 part 1, 6.2 and thus also meets the requirements for fire class DIN 4102-B1.

The article was tested according to the French Standard NF P 92-504 (Propagation de flamme) and thus also meets the requirements for class M1 according to NF P 92-503, 92-505 and 92-507. The article meets the requirements for class 1 according to EN 13773.

Thus meets also the requirements for class 1 according to the Italian Standards UNI 8456 and UNI 8457.

Thus meets also the requirements according to British Standard BS 5867 part 2 type C.

This article also meets the requirements according to the North American standard NFPA 701: 2010 Test Method #1 (based on the Test Reports Govmark, New York No. 2-94779, 2-94780, 2-94781).

This article also meets the requirements for class I according to the North American standard NFPA 260 for upholstered furniture (based on the Test Reports no. 10-002-775 A + B dated 24.11.2010).

This article meets the requirements according to EN 1021-1 and -2:2014 in conjunction with polyurethane foams with a density of more than 30 kg/m<sup>3</sup>.

Thus meets also the requirements according to British Standard BS 5852: ignition source 0 (cigarette), ignition source 1 (match) and ignition source 5 (crib 5) in conjunction with suitable combustion modified foams (at least 50 kg/m<sup>3</sup>).

Thus meets also the requirements according to the Italian standard UNI 9175, class 1 IM in conjunction with suitable combustion modified foams.

This article can meet the requirements according to FAR/JAR/CS 25.853 App. F to part 25, part I, § (a), (1) (ii) (vertical test, ignition time 12 sec).

Indorama Ventures Fibers Germany GmbH  
 (This document is valid without signature.)